



RESILIENT SPC LVT FLOORING SPEC SHEET & WARRANTY GUIDE

Construction: Layered Plank Consisting of UV coating, wear layer, décor film, vinyl and IXPE backing

Overall Thickness: 5.5mm (nominal)

Wear Layer Thickness: 0.3mm (12 Mil)

Size: Various

Locking System: Click

Edge: Micro Bevel

Backing: Attached 1.5mm IXPE Back

Noise Control: IIC: 65 / STC: 62

Gloss Level: Matt

Use: Residential, Commercial

Surface Texture: Wood Grain Embossed

Packing Carton Size: Various

Pieces Per Carton: 10

HUD/FHA Requirements: Exceeds

Warranty: 25 Years Residential, 5 Year Limited Light Commercial

Recycling: Suitable

LIMITED 25 YEAR RESIDENTIAL WARRANTY

Aspen Spring Flooring warrants that its Resilient Flooring will be free from manufacturing defects and, for 25 years following the date following the date of purchase, under normal household conditions , will not:

- Permanently indent
- Rip, tear or gouge
- Wear through the wear layer so that the printed pattern or design of the floor is altered

LIMITED 5 YEAR LIGHT COMMERCIAL WARRANTY

Aspen Spring Flooring warrants that its Resilient Flooring will be free from manufacturing defects and, for 5 years following the date of purchase, under normal commercial use, will not:

- Permanently indent
- Rip, tear or gouge
- Wear through the wear layer so that the printed pattern or design of the floor is altered